



888-968-3030

OutputOptions

DOCUMENT PRINTING SOLUTIONS AND SUPPLIES

AutoSeal® FD 2000

PRESSURE SEALER

Standard Features

- **Drop-In Feed System:** A drop-in three roller feed system produces dependable feeding of forms with no paper fanning required.
- **Six-Digit Resettable Counter:** Provides maximum audit control.
- **Paper Jog Control:** Allows operators to jog forms through before operation.
- **14" Form Length Capability:** Flexibility to process even and uneven panel forms up to 14" in length.
- **Desktop Design:** A sleek desktop design made with office usage in mind.
- **L.E.D. Indicators:** Notifies the operator when the power is on, a cover is open, the paper runs out and if a fault occurs.
- **Noise Reduction:** Top and side covers are insulated to reduce operating noise.
- **Fold Types:** "Z", uneven "Z", "C", half folds and custom forms.

Options:

- **P2000:** Cost saving package that includes the FD 2000, 18" conveyor and cabinet.
- **4' High Capacity Conveyor w/ Photo Eye:** Allows for neat and sequential stacking of up to 1,500 processed forms.
- **18" Conveyor w/ Photo Eye:** Allows for neat and sequential stacking.
- **Locking Cabinet:** Fully enclosed for storage
- **400 Series Jogger:** Reduces static electricity and aligns forms for proper feeding
- **FD 2000-35 Reverse Stacking Conveyor:** Allows for A-to-Z input and A-to-Z output.

For more information contact:

Tel: 888.968.3030

Fax: 775.924.7964

E-mail: info@output-options.com

Website: www.output-options.com

16 Kingston Road, Unit #8 • Exeter, NH 03833



Shown with optional cabinet and 18" conveyor

The AutoSeal® FD 2000 folder/sealer is a powerful desktop model designed to process your pressure sensitive self-mailers. An easy to use touch-pad control panel and three roller feed system makes this product both practical and dependable. Up to 150 forms can be loaded in the hopper and processed at speeds up to 7,000 per hour. The FD 2000 also comes with an optional fully enclosed cabinet for storage and a conveyor with photo-eye for neat and sequential stacking of processed forms.

Flexible

The FD 2000 handles a variety of documents up to 8 1/2" x 14" including checks, invoices, school reports, tax forms and appointment notices. Pressure seal mailers can be used for virtually any application that can be printed on one form.

Powerful


The FD 2000 processes forms at a rate of up to 7,000 sheets per hour and can hold up to 150 - 24# forms in the feed hopper. Combined with a duty cycle of up to 25,000 forms per month, the FD 2000 offers an economical and reliable solution for departmental post processing.



User friendly control panel

Pressure Seal Solution

The AutoSeal® FD 2000 combined with a laser printer and pressure seal forms create a secure, time saving and efficient solution for paper processing.



Standard "Z" Fold Process

Ease of Operation

The FD 2000 is set up for user friendly operation. Simply set your folds according to the clearly marked settings on the fold plates, load your forms, press start and you're on your way. The FD 2000 has indicators for power on, fault detection, paper out and cover open for operator convenience. It also includes a six-digit counter for audit control.



Standard Catch Tray

Specifications:

Hopper Capacity:	Up to 150 Sheets 24# (90gsm)
Fixed Speed:	Up to 7,000 sheets per hour - based on 11"(279mm) "Z" fold
Paper Size:	Up to 8.5" W x 14" L (216 W x 356 L mm)
Power:	FD Model: 120 Volts AC 50/60Hz FF Model: 220 Volts AC 50/60Hz
Duty Cycle:	Up to 25,000 per month
Dimensions:	25.75" L x 16.5" W x 14.25" H (65 L x 42 W x 36 H cm)
W/ 18" Conveyor & Cabinet:	46" L x 22" W x 44" H (117 L x 56 W x 112 H cm)
Weight:	88.5 lbs (40 kg)
Document Sequence:	Standard sequence is A-to-Z input, Z-to-A output. Optional FD 2000-35 reverse conveyor available for A-to-Z output.
Certifications:	UL and CUL approved CE applied for



A 400 Series Jogger is a recommended option that reduces static electricity from forms and aligns them for proper feeding